



Lackfabrik Irmgard Sallinger GmbH

Technical data sheet

08/2005

IRSA CARE OIL

Use and Characteristic:

For maintenance of oiled surfaces with normal to heavy duty wear and tear ; wood-, bamboo-, cotto- and cork surfaces, in interior design; non-waxed. IRSA Care Oil is applicable for maintenance and cleaning at the same time on surfaces treated with oils. Generally carry out a patch test first.

Instruction and Preparation:

Surfaces to be treated must be completely clean and free of sand or dust (sanding effect). Clean very dirty surfaces with IRSA Soap Cleaner or IRSA Base Cleaner G88 first and proceed after approx. 24 hours drying time at the earliest.

Optimal Maintenance of the Surface (frequency depends on optic appearance)

Manual maintenance:

First remove high solid dirt dry or with IRSA Soap Cleaner. Shake IRSA Care Oil well before use, apply fine dosed on a pre-impregnated IRSA Oil-tissue and wipe the **dry** surface. Depending on demand (e.g. high solid dirt, mat or slightly grey appearance), apply IRSA Care Oil directly on the dry surface thin end evenly. After 10 minutes work-in time use the IRSA Blitzboj-wiper and beige pad for dry rub-in of eventually surplus rests of IRSA Care Oil.

Maintenance by machine (one-disc-sanding machine):

First remove high solid dirt as mentioned above. Shake IRSA Care Oil well before use, apply fine dosed and evenly on the **dry** surface. Following rub-in thoroughly by machine with a beige pad. For high adhesive dirt use a green pad and remove the dirt immediately with a soaking fleece-tissue or IRSA Oil-tissue (e.g. placed under the green pad) and immediately remove after etching.

Cautions:

With arising of mat, worn-off parts or punctual spots on the surface, re-treat with the IRSA Oil-tissue/beige pad and IRSA Care Oil. Avoid wet oil-films or splashes on the surfaces to prevent a film-forming by the IRSA Care Oil. Care for good air condition. Do not walk on the treated surface as long as pure applied IRSA Care Oil -tracks are visible. Air conditions and temperature from +18°C speed up the drying process. The drying time of the pure and directly applied IRSA Care Oil is at least 6 hours. Re-polish the surface during the drying process with a white pad
Drying time indications refer to normal temperature-conditions of + 20°C and relative air-humidity of 55%.

Subsequent oiling:

Not only dirt will be removed with IRSA Soap Cleaner during the cleaning processing, also the IRSA Oil by-and-by. Therefore re-oil the surface depending on demand, e.g. if the wood appears mat grey or becomes susceptible for dirt. Treat the floor with the same IRSA Care Oil as used for the first application and follow the instructions of the technical data sheets and labels of all IRSA oils.

For long-lasting value of the floor, follow the maintenance-instructions of the IRSA oiled and waxed surfaces.

Total Consumption-experiences for one Care-Oil- treatment

depending on way of application approx. 10-25ml/m², i.e. 0,5l of IRSA Care Oil lasts for approx. 20m² oiled surface.

Storage:

Shelf life in unopened original container for at least 10 months.

Further information available on the safety data sheets and labels.

WGK 1 water-pollution class

The advice given by us in word, writing and endeavour for the technical application is supplied to our best knowledge, but may, however, only be regarded as an indication without any obligation and does not exempt you from examining the supplied products yourself, if they are suitable for the procedure and purposes intended. Application, use and processing of the products are not within our range of control and supervision, but are at your responsibility exclusively. It goes without saying that we guarantee products of high and good quality, according to the samples. With the publishing of new information the earlier technical data sheets loose validity.